

# SDH 64

# SIMAG

## 58 kg Self-contained Ice Machine

Complete range: SDH 18 – SDH 24 – SDH 30 – SDH 40 – SDH 50 – SDH 64

### Technical features

- Stainless steel bodywork - scotch brite
- Vertical pump
- Built-in cleaning system
- Easily accessible components
- Low power and water consumption
- Optimum ratio between ice production and bin capacity
- Reduced dimensions
- Double defrosting system
- Refrigerant R290



### Internal bin capacity



20 kg of ice



950 cubes

### Type of ice

Hollow Cubes



21 gr.



### Machine dimensions

#### Voltage

230/50/1 Standard version

Net size WxDxH 485 x 575 x 805 mm

Net weight 48 kg

Shipping size WxDxH 550 x 640 x 940 mm

Shipping weight 57 kg

### Technology and Certifications



SIMAG

Via Lainate 31 - 20010 Pogliano Milanese - (Milano) Italy

Tel. +39 02 93960323

e-mail: sales@simag.it

[www.simag.it](http://www.simag.it)

# SIMAG

Complete range: SDH 18 –SDH24 –SDH 30 –SDH 40 –SDH 50 – SDH 64



|                    | Minimum | Maximum |
|--------------------|---------|---------|
| Air temperature    | 10°C    | 43°C    |
| Water temperature  | 5°C     | 38°C    |
| Water pressure     | 1 bar   | 5 bar   |
| Electrical voltage | -10 %   | +10 %   |

| Model                                              | Voltage  | Daily production kg |           | Power input Watt (*) | Refrigerant |           | Fuse A | Consumptions (**) |          |           |
|----------------------------------------------------|----------|---------------------|-----------|----------------------|-------------|-----------|--------|-------------------|----------|-----------|
|                                                    |          | 10°C/10°C           | 21°C/10°C |                      | Type        | Charge kg |        | kWh/ 100kg        | kWh/ 24h | Water l/h |
| SDH 64 A                                           | 230/50/1 | 58                  | 54        | 460                  | R290        | 0.130     | 10     | 19.78             | 8.9      | 5.0       |
| SDH 64 W                                           | 230/50/1 | 60                  | 56        | 350                  | R290        | 0.130     | 10     | 13.92             | 7.1      | 67.6      |
| (**) Water Consumption: at 32°C Air and 21°C Water |          |                     |           |                      |             |           |        |                   |          |           |
| (*) Power Input: at 43°C Ambient Temperature       |          |                     |           |                      |             |           |        |                   |          |           |