



SILVERLINK 600

PRODUCT OPTIONS AND ACCESSORIES

- BA114 BASKET 1/2 PASTA
- BA116 BASKET L/H 1/4 PASTA
- BA112 BASKET PASTA
- BA115 BASKET R/H 1/4 PASTA
- CC6 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal with Doors - W 600 mm
- CN6 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 600 mm
- SLS6 Lincat Silverlink 600 Free-standing Floor Stand - for units W 600 mm
- HC6 Lincat Silverlink 600 Free-standing Heated Open-Top Pedestal with Doors - W 600 mm - 0.5 kW
- HCL6 Lincat Silverlink 600 Free-standing Heated Pedestal with Legs and Doors - W 600 mm - 0.5 kW

PRODUCT FEATURES

- Delivering perfect pasta, time after time
- Front mounted controls ensure safe working practice
- Hinging element with safety cut-out provides easy access to tank for cleaning
- Thermostatic control maintains accurate water temperature
- Enhanced resistance to punishing salt and starch corrosion with high quality grade 304 stainless steel tanks, basket support plates, and corrosion-resistant elements
- Front drain taps with straight drain pipes for fast, easy drainage of water - and no blockages
- Lid to reduce heat up time and also cover tanks when not in use
- Convenient twin electrical cables on PB66 twin tank model allow you to plug in to standard 13 amp sockets

WEIGHTS & DIMENSIONS

Width	600 mil
Depth	600 mil
Height	330 mil
Weight	22.8 kg

SHIPPING DETAILS

Ship Width	70 cm
Ship Depth	70 cm
Ship Height	49.5 cm
Ship Weight	25.08 kg
Number of Shipment Parcels	1
Ship Method	Small Parcel (FedEx, UPS, DHL)
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

WATER, PLUMBING, AND DRAINAGE SPECS

Water Line Required	No
Drain Line Required	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Type	Electric	Electrical Phase	1-Phase
Electrical Amps Per Conductor	2 x 13.0	Electrical Plug Type	UK 3-Pin Plug
Electrical Total Amperage	26 A	Number of Electrical Plugs	2
Electrical Volts	230V	Electrical Connection Type	Cord and Plug
Electrical Total Wattage	6000 W	Number of Electrical Conductor Wires	2
Electrical Kilowatts	6 kW	Electrical Remarks	Single

ADDITIONAL SPECIFICATIONS

Capacity Volume	22 l	Number of Vats (batteries)	2
Construction Materials	Stainless Steel	Overflow Prevention	No
Control Type	Mechanical	Ventless Cooking Technology	No
Mixing Valve	No	Water Fill	Manual
Number of Baskets	0		

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING

